

## SUBMITTAL

TYPE: NLAP ASME PRESSURIZED EXPANSION TANKS FOR HEATING & COOLING SYSTEMS


	MODELS: NLAP 40 THRU NLAP 1100 Submittal Sheet No. N-3355 Date: 9-4			
JOB	Wessels Representative			
Unit Tag No	_ Submitted By Da	ate ate		
DESCRIPTION  Wessels Type NLAP Tanks are ASME removable bladder type pre-charge expansion tanks. They are designed to absorb the expansion forces and control the pressures in heating/cooling systems. The water is contained in the one-piece molded heavy-duty butyl bladder preventing tank corrosion and watterlogging problems. NLAP expansion tanks reduce tank	CONSTRUCTION Shell: Carbon Steel Bladder: Heavy Duty Butyl  PERFORMANCE LIMITATIONS Maximum Design Pressure: 125 PSIG* Maximum Design Temperature: 240°F			
sizes up to 80%.	*200 & 250 PSIG available			

## SCHEDULE


Model Number	Tank Volume Gallons	Tagging Information	Quantity
NLAP 40	11		
NLAP 60	15		
NLAP 100	25		
NLAP 150	39		
NLAP 220	58		
NLAP 325	85		
NLAP 400	104		
NLAP 560	147		
NLAP 600	158		
NLAP 700	185		
NLAP 815	215		
NLAP 950	250		
NLAP 1100	290		

TYPICAL SPECIFICATIONS			
Furnish and install as shown on the plans a	gallon	" diameter X	<b>;</b> ;
(high) pre-charged steel expansion tank with a one pie system connections and a .302" – 32 charging valve of the tank to meet system requirements. The tank mus and Pressure Vessel Code.	connection (standard tire v	alve) to facilitate the on-site cha	arging of
Each tank shall be Wessels model number NLAP	or approve	ed equal.	

## **ASME EXPANSION TANKS - PRESSURIZED**







NLAP 100 thru NLAP 1100

## **DIMENSIONS & WEIGHTS**

	Dimensions in Inches					
Model Number	Dia. A	Height B	System Connection C	Charging Valve D	E	Approx. Ship Wt. (lbs)
NLAP 40	12"	26.5"	2/45		•	42
NLAP 60	14"	26.1"	3/4"		-	52
NLAP 100	4.00	32.1"	1"		12"	77
NLAP 150	16"	48.5"				115
NLAP 220	20"	48.5*			16"	170
NLAP 325	24"	50.5"		.302" -32NC	20"	225
NLAP 400		57.5"	,	-32NC		250
NLAP 560	30"	53.0"	·		24"	325
NLAP 600		58.0"	1 1/2"			350
NLAP 700		66.0"	1 1/2			400
NLAP 815	36"	58.0"			30"	475
NLAP 950		66.0"				540
NLAP 1100		75.0"				625

Note: Tanks are factory pre-charged at 12 psi and field adjustable California code-sight glass available on request

